

## ZG600





Used in food filling, mechanical grinding and polishing liquid, chemical liquid transportation, water treatment and other large flow transmission

- High-power DC motor drive, strong load capacity.
- The body shell is made of stainless steel, which is sturdy and durable.
- Equipped with large flow YZ35, YZ35-13L, YZ35LS pump head, the maximum transmission capacity is 12L.
- Two-way high torque, can cascade multiple pump heads.

Max Flow: 12000mL/min

Max speed : 600rpm

Pump head/hose flow parameter table:

Pump head	Model	Tube	ID(mm)	Wall thickness (mm)	Max flow (mL/min)	Max speed (rpm)
	YZ35	73#	9.6	3.3	7400	600
		82#	12.7	3.3	12000	
	YZ35-13L	73#	9.6	3.3	7400	
		82#	12.7	3.3	12000	
	YZ35LS	73#	9.6	3.3	7400	
		82#	12.7	3.3	12000	

**Test conditions:**

- 1.Flow data testing environment for room temperature 20-25 °C, relative humidity is not more than 80%, altitude is not more than 1500 meters.
- 2.The test is measured using a straight-through tube, suction range of 0.5 meters, the head is not more than 0.5 meters, the total length of the tube is not more than 1.5 meters (inlet end + outlet end + test end).

**The above data test environment for normal temperature and pressure, the test fluid is water, the data is for reference only, please prevail in practice.**

\* For specific needs, please consult Chuangrui Company.